

Features:

- 1、 Multi-Color TFT Display, four display modes, have big-font display, digital display and plethysmogram display.
- 2、 Change directions manually according to patient observe needs.
- 3、 Audible alarm function, Alarm lamp display and heart rate pulse synchronization;
- 4、 Low power consumption, 50 hours continuous to work.
- 5、 It has the function of Perfusion Index to better get the pulse oxygen perfusion;
- 6、 When the battery voltage is too low, which may affect the normal use, there will be a low voltage warning indication in the visual window;
- 7、 Automatic power off when no signals for 8s
- 8、 Small and light weight, convenient to carry.

Technical Specification

- 1、 Display type: Multi-Color TFT display; 1 inch
- 2、 Spo2 measurement range: 35%-99% PR Measurement range: 30-240BPM
- 3、 Resolution: $\pm 1\%$ for Spo2; ± 1 BPM for Pulse rate
- 4、 Accuracy: $\pm 1\%$ (90%-99%) ; 70%-89%, $\pm 2\%$; unspecified($\leq 70\%$) for spo2
- 5、 Low perfusion: $\leq 0.4\%$
- 6、 Power: Two of 1.5(AAA Size) alkaline batteries
- 8、 Power consumption: < 30 mA
- 9、 Automatic power-off: The product will automatically power off when no signals for 8s.
- 10、 Operation Environment
Operation Temperature: $5^{\circ}\text{C}\sim 40^{\circ}\text{C}$
Humidity: 30%~90%
Air pressure: 70kPa~106kPa

Size:

63mm X 41mm X 31mm

Picture:

